

Australia
14 September 2017

JAMES BAY DRILLING UPDATE - SIGNIFICANT MINERALISATION EXTENDED

Galaxy Resources Limited ("Galaxy" or the "Company") (ASX: GXY) is pleased to announce further assays from its 2017 drilling campaign at its James Bay Project ("James Bay"), Quebec, Canada.

In late March, the Galaxy James Bay team commenced a ~33,000m diamond drilling campaign to extend and develop the existing James Bay spodumene resource in Quebec, Canada - the program is now complete. All assays are expected to be finalized by the end of September 2017.

All intercepts below are reported downhole.

Highlights from this round of drilling and assay are:

- **56.6m** at 1.61% Li₂O from 89.3m to 145.9m (drill hole JBL17- 09)
- **49.6m** at 1.60% Li₂O from 17.0m to 66.6m (drill hole JBL17- 30)
- **34.5m** at 1.63% Li₂O from 68.8m to 103.3m (drill hole JBL17-104)
- **35.9m** at 1.54 % Li₂O from 2.0m to 37.9m (drill hole JBL17-105)
and 53.5m at 1.72 % Li₂O from 68.5m to 122.0m
- **41.0m** at 1.81 % Li₂O from 25.8m to 66.8m (drill hole JBL17-106)
and 88.4m at 1.46 % Li₂O from 204.1m to 292.5 m
- **34.2m** at 1.29 % Li₂O from 86.0m to 120.2m (drill hole JBL17-60)

Assays (Tables 1 and 2, below) have been received for a further 49 diamond holes for 10,111m of NQ drilling (collars, Table 1, below). Drilling has been both resource infill and resource extensional in type. All drilling is diamond (core). Pegmatites outcrop at surface and the drill program has targeted approximately 1,850m of pegmatite outcrop westward of the James Bay Highway. The first three drill holes east of the highway returned economic grades in pegmatite. The resource remains open and largely untested east of the James Bay Highway.

Thicker pegmatites at the western extremity of the known mineralization remain open and untested below the limits of the current drilling. The now-completed drilling program will be used for a mineral resource re-estimate and upgrade, which is expected to be finalised by the end of October 2017.

Galaxy's Managing Director and CEO, Anthony Tse, commented *"The results from this last set of assays are very good and reaffirm the potential of James Bay, as a long-life high grade spodumene project. We look forward to the outcome of the resource upgrade which will follow. The Project Notice, which outlines the scope of the project, is expected to be submitted shortly to the relevant departments in both the Quebec Government and the Federal Government of Canada. "*

Further assay results will be released as they are received over the coming weeks.

All results are listed in Table 2, below.

Figure 1: James Bay Spodumene Project – Plan View




Figure 2: James Bay Spodumene Project – Section View




Table1: Drill hole collar positions. Coordinates are in coordinate system NAD 83, Zone 18

Hole #	Length (m)	NAD83 mN	NAD83 mE	Azimuth	Dip
JBL17-09	192	5,789,879	357,247	155	77
JBL17-10	123	5,789,848	357,262	157	73
JBL17-27	180	5,789,528	357,670	145	45
JBL17-28	201	5,789,494	357,898	147	45
JBL17-29	201	5,789,450	357,890	115	45
JBL17-30	129	5,789,445	358,045	115	42
JBL17-32	81	5,789,528	358,071	113	45
JBL17-58	60	5,789,625	357,905	111	75
JBL17-104	282	5,789,546	357,820	145	45
JBL17-105	314	5,789,593	357,865	143	46
JBL17-106	303	5,789,620	357,907	152	43
JBL17-46	270	5,789,386	358,334	107	80
JBL17-47	243	5,789,415	358,554	116	59
JBL17-48	171	5,789,375	358,547	116	45
JBL17-49	141	5,789,399	358,516	127	77
JBL17-50	222	5,789,351	358,502	116	77
JBL17-51	207	5,789,329	358,416	103	73
JBL17-52	228	5,789,295	358,304	107	63
JBL17-59	168	5,789,457	358,223	104	50
JBL17-60	207	5,789,457	358,223	104	66
JBL17-98	243	5,789,373	358,456	106	77
JBL17-99	309	5,789,373	358,400	115	77
JBL17-100	234	5,789,422	358,240	111	67
JBL17-101	180	5,789,366	358,258	57	87
JBL17-102	231	5,789,333	358,200	110	90

Table 1 (Continued): Drill hole collar positions. Coordinates are in coordinate system NAD 83, Zone 18

Hole #	Length (m)	NAD83 mN	NAD83 mE	Azimuth	Dip
JBL17-61	240	5,789,351	358,649	119	68
JBL17-62	210	5,789,313	358,608	113	71
JBL17-64	243	5,789,235	358,528	111	61
JBL17-65	216	5,789,314	358,750	124	65
JBL17-68	258	5,789,197	358,633	117	66
JBL17-69	162	5,789,314	358,823	110	60
JBL17-72	270	5,789,172	358,701	112	65
JBL17-73	117	5,789,273	358,863	113	49
JBL17-74	144	5,789,225	358,849	114	50
JBL17-75	126	5,789,180	358,828	109	48
JBL17-97	231	5,789,270	358,644	116	60
JBL17-113	309	5,789,220	358,572	120	46
JBL17-114	305	5,789,158	358,620	122	50
JBL17-115	252	5,789,265	358,740	113	61
JBL17-116	240	5,789,333	358,773	120	60
JBL17-117	150	5,789,280	358,347	106	62
JBL17-118	231	5,789,332	358,350	104	71
JBL17-119	228	5,789,319	358,445	120	53
JBL17-120	162	5,789,412	358,483	126	75
JBL17-121	234	5,789,429	358,502	116	62
JBL17-95	201	5,789,042	358,858	107	44
JBL17-110	150	5,788,930	359,315	110	46
JBL17-111	159	5,788,937	359,428	107	44
JBL17-112	153	5,788,915	359,559	106	44

Table 2: New Assay results from James Bay. All results are downhole lengths, assay by ALS Canada, ore-grade four acid digest followed by ICP-AES open beaker.

Hole #	From (m)	To (m)	Metres	Grade (Li20 %)
JBL17-09	89.3	145.9	56.6	1.61
<i>incl.</i>	143.3	145.9	2.6	3.75
	165.2	171.2	6	2.37
JBL17-10	39.7	72.7	33	0.73
JBL17-27			NSA (no significant assay)	
JBL17-28	77.8	85.8	8	1.21
JBL17-29	159.3	168.3	9	1.21
JBL17-30	17	66.6	49.6	1.6
JBL17-32	11.6	19.9	8.3	1.62
	21.9	32.3	10.4	1.83
	42.5	64.4	21.9	1.57
JBL17-58	1.9	35.8	34	1.78
	25.9	30.4	4.5	2.47
JBL17-104	68.8	103.3	34.5	1.63
	173.5	191.1	17.6	1.6
JBL17-105	2	37.9	35.9	1.54
	68.5	122	53.5	1.72
	201	225	24	1.79
<i>incl.</i>	220.5	223.2	2.7	3.28
	236.6	245.6	9	1.8
JBL17-106	2.7	22.9	20.2	1.61
	25.8	66.8	41	1.81
	204.1	292.5	88.4	1.46
JBL17-111	137.5	141.2	3.7	1.54
JBL17-112	27.3	37.5	10.2	1.15
	78.7	81.4	2.8	1.32
JBL17-113	90.2	95.8	5.6	1.35
	140.5	145.6	5.1	1.85
	157.8	173.9	16	1.74
	198.8	201.2	2.4	1.33
	212.5	214.9	2.4	1.52
	240	250.3	10.3	1.35
	288.8	293.9	5.1	1.78

Table 2 continued: New Assay results from James Bay. All results are downhole lengths, assay by ALS Canada, ore-grade four acid digest followed by ICP-AES open beaker.

Hole #	From (m)	To (m)	Metres	Grade (Li20 %)
JBL17-46	127.8	141.1	13.3	0.99
	151	177.7	26.7	0.81
	188.1	192.6	4.5	1.39
JBL17-47	15.1	26.6	11.5	1.64
	36.9	49.6	12.6	1.72
	63.4	65.9	2.5	0.94
JBL17-48	148.2	164.8	16.7	1.47
	210.7	217.6	6.9	1.4
	226.4	229.9	3.4	1.38
JBL17-49	15.5	39.7	24.2	1.91
	45.3	55.9	10.6	1.57
	59.7	64	4.3	1.23
JBL17-50	86.3	91.1	4.7	1.12
	128	133.2	5.2	1.1
	143.4	149.4	6	1.37
JBL17-51	2.7	8.5	5.8	1.73
	56.5	63.7	7.2	1.63
	73.9	101.1	27.2	1.61
JBL17-52	114.9	119	4.1	1.46
	28.7	35	6.3	1.14
	60	64	4	1.37
JBL17-59	72.8	97.2	24.5	1.45
	108	118.9	11	1.92
	173.4	177.2	3.8	1.31
JBL17-60	192.2	206.3	14.1	1.69
	115.7	118.1	2.3	1.26
	135	140.5	5.5	0.93
JBL17-55	151.5	153.8	2.3	1.15
	NSA			
	75	97.5	22.5	1.47
JBL17-56	105.3	117	11.7	1.12
	130.3	142.3	12	1.47
	148	150.3	2.3	2.06
JBL17-57	86	120.2	34.2	1.29
	127.4	137.9	10.6	1.57
	145.7	157.5	11.8	1.52
JBL17-58	164.2	169.5	5.3	1.23

Table 2 continued: New Assay results from James Bay. All results are downhole lengths, assay by ALS Canada, ore-grade four acid digest followed by ICP-AES open beaker.

Hole #	From (m)	To (m)	Metres	Grade (Li20 %)
JBL17-61	27	34.8	7.8	1.4
	66.7	74.7	8	1.73
	83.2	89	5.8	1.59
	148.5	157.8	9.3	1.49
	165	182.2	17.2	1.28
	189.9	192.6	2.7	0.94
	214.7	221.7	7	1.31
JBL17-62	12.2	30.9	18.7	1.53
	72.2	79	6.8	1.39
	86	87.6	1.6	1.3
	95.2	98.4	3.2	1.29
	104.4	114.7	10.3	1.42
	128.1	141.7	13.6	1.41
	194.3	202	7.7	1.26
JBL17-64	105.2	107.1	1.9	1.54
	141.2	146.6	5.4	1.3
	158.6	162.9	4.3	0.89
	185.4	189.6	4.2	1.39
	215.8	223.7	7.9	1.63
	53	62.9	9.9	1.47
	110.9	115.4	4.5	1.83
JBL17-65	184	186.5	2.5	2.6
	125.1	138.4	13.3	1.6
	218.6	229.2	10.6	1.27
JBL17-68	245.2	246.6	1.4	1.02
	41.6	55.9	14.3	1.13
	61.6	77.3	15.7	1.68
JBL17-72	158.3	171.1	12.8	1.28
	214.5	226.8	12.3	1.32
	44.3	53.5	9.2	1.12
JBL17-74	21.4	32.7	11.3	1.31
JBL17-75	25.3	43	17.7	1.6

Table 2 continued: New Assay results from James Bay. All results are downhole lengths, assay by ALS Canada, ore-grade four acid digest followed by ICP-AES open beaker

Hole #	From (m)	To (m)	Metres	Grade (Li20 %)
JBL17-95	120.6	127.7	7	1.48
	148.9	155.5	6.7	1.23
	186	188.9	2.8	0.84
JBL17-97	3.6	11.8	8.2	1.64
	157.3	166.6	9.3	1.89
	206.6	213.8	7.2	1.32
JBL17-98	34.2	47	12.9	1.70
	102.5	105.9	3.3	1.74
	120	145.9	25.9	1.50
JBL17-99	155.7	159.5	3.8	1.91
	75.9	96.5	20.6	1.26
	103.7	106.3	2.6	1.34
JBL17-100	78.5	87.5	9	1.82
	115.5	142.2	26.7	1.62
	174	177.9	3.8	1.13
JBL17-101	201	214	13	1.34
	156.5	170.2	13.7	1.44
	195.8	200.5	4.7	1.03
JBL17-102	210.9	215	4.1	0.85
	8.6	19.5	10.9	1.68
	60	62.4	2.5	1.48
JBL17-110	71.3	74.7	3.4	0.93
	76.7	83.5	6.8	1.40
	107.8	109.6	1.8	1.61
JBL17-114	121	124.6	3.6	0.72
	150	151	1	1.43
	156.5	159.2	2.7	0.95
	169.5	174.4	4.8	1.06
	185.5	193.3	7.8	1.93

Table 2 continued: New Assay results from James Bay. All results are downhole lengths, assay by ALS Canada, ore-grade four acid digest followed by ICP-AES open beaker.

Hole #	From (m)	To (m)	Metres	Grade (Li20 %)
JBL17-115	38.6	40.9	2.3	1.43
	48	58.5	10.5	1.71
	79.3	101	21.8	1.25
	128	132.4	4.4	1.32
	147.1	151.6	4.5	1.39
	213.8	234.6	20.8	1.19
	238.6	241.8	3.2	1.79
JBL17-116	33.7	36.4	2.8	0.88
	41	49.4	8.4	1.53
	63	69.9	6.9	1.49
	76.2	77.9	1.8	1.21
	93.3	99	5.7	1.45
	107.3	113.6	6.3	1.55
	219.8	227	7.3	1.58
JBL17-117	228.1	230.3	2.1	0.5
	NSA			
	JBL17-118	105	107.7	2.7
		109.9	117.2	7.3
		132.9	134.2	1.3
		166.3	168.8	2.5
JBL17-119	83.5	94.9	11.4	1.84
	115.6	117.4	1.8	1.7
	130.7	132.8	2.1	1.56
	159	161.6	2.6	1.55
	181	187.5	6.4	1.96
	213.7	217.3	3.6	1.58
	JBL17-120	14.5	24.7	10.2
		30.6	43.5	12.9
		106	123.5	17.5
JBL17-121	1.1	3	1.9	1.54
	6.7	16.8	10.1	1.63
	18.5	20.2	1.8	1.54
	46.3	49.9	3.6	0.38
	71.5	88.4	17	1.74
	102.6	104	1.4	1.24
	191.3	203.3	12	1.75
	210	211.1	1.1	1.42

ABOUT THE JAMES BAY PROJECT

The James Bay Pegmatite swarm is located 10km south of the Eastmain River and 100 kilometers east of James Bay. The property is accessible by paved road from the James Bay Road which cuts through the property close to the 381km road marker on the highway Route/109 from Val d'Or, Quebec, Canada. Val d'Or is approximately 526km westward from Montreal, Quebec. A large, multi-service truck stop is located at marker 381. Discovered in the 1960's and then known as the Cyr property the site consists of a swarm of 33 pegmatite dykes that belong to the rare-element 'class', the LCT (Li-Cs- Ta) 'family' and the albite-spodumene 'type' per the classification by Cerny (1991). Two new major pegmatite dykes have been discovered in this current campaign as well as smaller swarms eastward of the known extent. The mineralised pegmatite is open at depth and to the east. The lithium bearing mineral contained in the pegmatites is spodumene $\text{LiAl}(\text{Si}_2\text{O}_6)$, a member of the pyroxene group of minerals. A classified resource was reported at cut-off grade of 0.75% Li_2O of 11.75Mt @ 1.30% Li_2O (Indicated) and 10.47Mt @ 1.20% Li_2O (Inferred) within a conceptual pit shell using a lithium carbonate price of USD 6,000/t, metallurgical and process recovery of 70%, mining and process costs of USD 64 per tonne and overall pit slope of 45 degrees. The current resource is based on 14,457m of diamond drilling and 201.3m of horizontal channel sampling. The pegmatite swarms have dip direction ~N 103 degrees E., dip steeply at ~60 degrees westward and forms a corridor of discontinuous dykes about ~4km in length and ~300m wide. This outcrop is to about 15-20m above the surrounding muskeg/swamp. This phase of drilling is complete.

ENDS

For more information, please contact:

Corporate

Nick Rowley
 Director – Corporate Development
 +61 455 466 476
 +61 (8) 9215 1700
 nick.rowley@galaxylithium.com

Media Enquiries (Australia)

John Gardner
 Citadel-MAGNUS
 +61 413 355 997 or +61 (8) 6160 4901
 jgardner@citadelmagnus.com

Media Enquiries (International)

Heidi So
 Strategic Financial Relations Ltd
 +852 2864 4826
 heidi.so@sprg.com.hk

About Galaxy (ASX: GXY)

Galaxy Resources Limited ("Galaxy") is an international S&P / ASX 200 Index company with lithium production facilities, hard rock mines and brine assets in Australia, Canada and Argentina. It wholly owns and operates the Mt Cattlin mine in Ravensthorpe Western Australia, which is currently producing spodumene and tantalum concentrate, and the James Bay lithium pegmatite project in Quebec, Canada.

Galaxy is advancing plans to develop the Sal de Vida lithium and potash brine project in Argentina situated in the lithium triangle (where Chile, Argentina and Bolivia meet), which is currently the source of 60% of global lithium production. Sal de Vida has excellent potential as a low-cost brine-based lithium carbonate production facility.

Lithium compounds are used in the manufacture of ceramics, glass, and consumer electronics and are an essential cathode material for long life lithium-ion batteries used in hybrid and electric vehicles, as well as mass energy storage systems. Galaxy is bullish about the global lithium demand outlook and is aiming to become a major producer of lithium products.

Competent Persons Statement

Information included in this announcement that relates to exploration results is based on and fairly represents information and supporting documentation prepared and compiled by Albert Thamm M.Sc. F.Aus. IMM (CP), who is a Corporate Member of the Australasian Institute of Mining and Metallurgy. Mr. Thamm is an employee of Galaxy Resources Limited. Mr. Thamm has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the Australasian Code for Reporting Exploration Results, Mineral Resources and Ore Reserves. Mr. Thamm and consents to the inclusion in the announcement of the matters based on this information in the form and context in which it appears.

The information in this report that relates to Mineral Resources at the James Bay Project is based on work completed by Mr. James McCann M.Sc. P. Geo, who is a Member of the Ordre des Geologues du Quebec, a Recognised Overseas Professional Organisation. Mr. McCann is an employee of Galaxy Resources Limited, and has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2004 edition of the 'Australian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr. McCann consents to the inclusion in the report of the matters based on his information in the form and context it appears. This information was prepared and first disclosed under the JORC Code 2004 and it has not been updated since to comply with JORC code 2012 on the basis that the information has not materially changed since it was last reported.

Caution Regarding Forward-Looking Information

This document contains forward-looking statements concerning Galaxy.

Forward-looking statements are not statements of historical fact and actual events and results may differ materially from those described in the forward-looking statements because of a variety of risks, uncertainties and other factors. Forward-looking statements are inherently subject to business, economic, competitive, political and social uncertainties and contingencies. Many factors could cause the Company's actual results to differ materially from those expressed or implied in any forward-looking information provided by the Company, or on behalf of, the Company. Such factors include, among other things, risks relating to additional funding requirements, metal prices, exploration, development and operating risks, competition, production risks, regulatory restrictions, including environmental regulation and liability and potential title disputes.

Forward looking statements in this document are based on Galaxy's beliefs, opinions and estimates of Galaxy as of the dates the forward-looking statements are made, and no obligation is assumed to update forward looking statements if these beliefs, opinions and estimates should change or to reflect other future developments.

Not For Release in the US

This announcement has been prepared for publication in Australia and may not be released in the United States of America. This announcement does not constitute an offer of securities for sale in any jurisdiction, including the United States, and any securities described in this announcement may not be offered or sold in the United States absent registration or an exemption from registration under the United States Securities Act of 1933, as amended. Any public offering of securities to be made in the United States will be made by means of a prospectus that may be obtained from the issuer and that will contain detailed information about the company and management, as well as financial statements.

JAMES BAY LITHIUM PROJECT, QUEBEC, CANADA.


Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> <i>Nature and quality of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i> <i>Aspects of the determination of mineralisation that are Material to the Public Report.</i> 	<ul style="list-style-type: none"> Diamond core, sawn ½ core. Chibourgamau Diamond Drilling Ltd. Sample length selected to match geological intervals and contacts to a maximum of 1.50m in length.
Drilling techniques	<ul style="list-style-type: none"> <i>Drill type</i> 	<ul style="list-style-type: none"> Diamond drilling, NW casing, NQ core, orientated.
Drill sample recovery	<ul style="list-style-type: none"> <i>Method of recording and assessing core and chip sample recoveries and results assessed.</i> <i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i> <i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i> 	<ul style="list-style-type: none"> Core recovery assessed vs drillers mark up. Samples are considered representative. Samples are selected on visual mineralogy. Half diamond core is produced for assay thus no loss or gain of fine material as in RC or RAB.


Criteria	JORC Code explanation	Commentary
Logging	<ul style="list-style-type: none"> <i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i> <i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography.</i> <i>The total length and percentage of the relevant intersections logged.</i> 	<ul style="list-style-type: none"> Logged geologically and geotechnically, with emphasis on pegmatite mineralogy. All core is photographed; logging is qualitative in nature and all core is logged.
Sub-sampling techniques and sample preparation	<ul style="list-style-type: none"> <i>If core, whether cut or sawn and whether quarter, half or all core taken.</i> <i>If non-core, whether riffled, tube sampled, rotary split, etc. and whether sampled wet or dry.</i> <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i> <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i> <i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i> <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i> 	<ul style="list-style-type: none"> Sawn ½ NQ core. All pegmatites are sampled. Sample types are consistent with prior sampling and drilling campaigns. Sampling demonstrated to be representative in prior sampling campaigns at NQ size. Sample size is appropriate given the grain size of the mineralogy sampled.

Quality of assay data and laboratory tests	<ul style="list-style-type: none"> <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> <i>For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i> <i>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i> 	<ul style="list-style-type: none"> Weigh, crush and pulverise at ALS Canada. Processed at ALS Val d'Or located at 1324 Rue Turcotte, Val d'Or, QC, Canada. Methods CRU-31,CRU-QC,LOG-21,SPL-21,WEI-21. Processed at ALS Vancouver located at 2103 Dollarton Hwy, North Vancouver, BC, Canada. Methods Li-OG63,ME-OG62o,PUL-31,PUL-QC. Four acid digest method OC62o. Analysis for lithium ore grade method Li-OC63. Li lower detection limit 0.005 % upper limit 10%, Std. tolerance 3.5%. This method is suitable for analyzing lithium in geological samples. A ~0.4g sample is first digested with HClO4, HF, and HNO3 until dryness. The residue is subsequently re-digested in concentrated HCl, cooled and topped up to volume. The samples are analyzed for Li by ICPAES spectroscopy. Method ICP_AES. Technique is total. Assayed at ALS Vancouver after sample preparation. Standards show acceptable levels of accuracy and precision.
---	--	--



Date Interval: 13-Jun-2017 to 13-Sep-2017

STATISTICS	All Data	LIGALA Data
Mean	1.0634	1.0641
Median	1.065	1.065
SD	0.0192	0.0196
%RSD	1.8055	1.8419
Max	1.105	1.105
Min	1.025	1.025
# Datapoints	159	111



Criteria	JORC Code explanation	Commentary
Verification of sampling and assaying	<ul style="list-style-type: none"> <i>The verification of significant intersections by either independent or alternative company personnel.</i> <i>The use of twinned holes.</i> <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> <i>Discuss any adjustment to assay data.</i> 	<ul style="list-style-type: none"> External audit of assay precision and accuracy. Existing resource and data stored as Maptek/Vulcan TM files with supporting spreadsheets. Primary data logged on paper, assay reconciled from csv. QA/QC data reported ex lab QA/QC compilation. No adjustments to assay data. Assay in Li reported to Li₂O. External audit trail login to ALS assay reporting system.
Location of data points	<ul style="list-style-type: none"> <i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i> <i>Specification of the grid system used.</i> <i>Quality and adequacy of topographic control.</i> 	<ul style="list-style-type: none"> Hand held GPS collars, re-surveyed at end of program. Down Hole survey, Reflex downhole system. Reported NAD 83, Zone 18N. Regional state DEM available to control surface topography and survey.
Data spacing and distribution	<ul style="list-style-type: none"> <i>Data spacing for reporting of Exploration Results.</i> <i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i> <i>Whether sample compositing has been applied.</i> 	<ul style="list-style-type: none"> Data spacing is irregular but designed to infill between and extend at depth extant resource drilling. The data spacing is sufficient to establish both geological and grade continuity. Samples are not reported as composites, rather as reported. Downhole survey has occurred every 3m downhole.

Criteria	JORC Code explanation	Commentary
Orientation of data in relation to geological structure	<ul style="list-style-type: none"> Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	<ul style="list-style-type: none"> Orientation of sampling, once corrected for dip, achieves unbiased sampling.
Sample security	<ul style="list-style-type: none"> The measures taken to ensure sample security. 	<ul style="list-style-type: none"> Detail audit trail available from ALS Canada. From dispatch, receipt through process to results.
Audits or reviews	<ul style="list-style-type: none"> The results of any audits or reviews of sampling techniques and data. 	<ul style="list-style-type: none"> Galaxy has reviewed the 2010 resource estimated by SRK Canada. A 2nd CP/QP has audited laboratory QA/QC standards for accuracy and precision.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<ul style="list-style-type: none"> <i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i> <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a license to operate in the area.</i> 	<ul style="list-style-type: none"> This project is in the west-central part of Township No. 2312 in North-western Quebec. It is 2 kilometers south of the Eastmain River and 100 kilometers east of James Bay. The property is readily accessible by paved road as the regional highway cuts through the property close to road marker kilometer 381, which is 381km from the town of Mattagami where there is an airport and mining related infrastructure. Galaxy Lithium Canada (Inc) 20%, Galaxy Lithium Ontario (Inc) 80%. (50 claims). Galaxy Lithium Canada (Inc) 100%. (4 claims). The Quebec state government Mining and cadastre online website indicates the site is free of major and minor environmental impediments. Detail tenement and claims list has been reported in the GXY June 2017 Quarterly report and all tenements are in good order.

Criteria	JORC Code explanation	Commentary
Exploration done by other parties	<ul style="list-style-type: none"> <i>Acknowledgment and appraisal of exploration by other parties.</i> 	<ul style="list-style-type: none"> The claims were first staked in 1966 by Mr. J. Cyr and were optioned by SDBJ in 1974, who after conducting some exploration on the property, returned it to Mr. Cyr. Prior to this, Mr. Cyr first discovered spodumene pegmatite outcrops on the property in 1964. There had been little modern exploration conducted on the property, until prior operator Lithium One started drilling in 2008. Significant trenching and drilling had been completed in the late 1970's. The Company's drilling in 2008 and 2009 confirmed the presence of wide pegmatite intersections, numerous swarms over several hundred meters of lateral extent, and about 2km in strike length to a depth of 100 to 150 meters. Three diamond drill holes, for a total of 383m, were completed on the property in 1977 and these confirmed the presence of spodumene mineralization to a depth of approximately 100 meters. Lithium One drilled the property in 2008-2009 resulting in a classified NI43-101 resource. Lithium One also undertook ~700m of channel samples in 2009. Between 2008 and 2010 Lithium One completed 102 diamond core boreholes to delineate 31 pegmatite dykes.

Criteria	JORC Code explanation	Commentary
Geology	<ul style="list-style-type: none"> <i>Deposit type, geological setting and style of mineralisation.</i> 	<ul style="list-style-type: none"> The James Bay Lithium Project lies in the north-eastern part of the Superior geological province, within the Eastmain greenstone belt (Lower Eastmain Group) which consists of amphibolite-grade mafic to felsic metavolcanics, meta-sediments and minor gabbroic intrusions. On the property metavolcanics of the Komo formation occur north of the pegmatite intrusions. The Auclair formation consists mainly of para-gneisses probably of sedimentary origin, which surround the pegmatites from the north-west to the south-eastern extremities. The greenstones are surrounded by migmatites and gneiss of Archean Age. The individual pegmatite bodies are mostly irregular dykes or lenses attaining up to 150 meters in width and over 100 meters in length. These cross-cut at a high angle to the local foliation and presumed bedding of the intruded rocks. The pegmatites are generally perpendicular to the trend of the corridor; they form small hills reaching up to 30 meters above the surrounding swamps/muskeg. The mineralization belongs to the rare-element class LCT (Li-Cs-Ta) family and the albite-spodumene type. In the case of the Cyr-Lithium deposit, spodumene-bearing pegmatites are likely the most differentiated dykes distant from the cogenetic Kapiwak Pluton intrusion located farther south In September 2008, Lithium One completed an 18-hole diamond drill program, with drill holes spaced at 100 metres apart, which totaled 1,096m. In 2009 a further 84 drill holes at 50-65m spacing was completed for 12,380m.

Criteria	JORC Code explanation	Commentary
Drill hole Information	<ul style="list-style-type: none"> • A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> ◦ easting and northing of the drill hole collar ◦ elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar ◦ dip and azimuth of the hole ◦ down hole length and interception depth ◦ hole length. • If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	<ul style="list-style-type: none"> • Drill hole collars provided in the text above. • No collar information is excluded. • Interception depths provided in Tables above.

Criteria	JORC Code explanation	Commentary
Data aggregation methods	<ul style="list-style-type: none"> <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</i> <i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i> <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i> 	<ul style="list-style-type: none"> No metal equivalents are used. Assays reported are down hole. Assays reported ex ALS as Li (ppm), standard oxide conversion to Li2O percent. Continuous result of the interval quoted, downhole. Data is aggregated down hole length.
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> <i>These relationships are particularly important in the reporting of Exploration Results.</i> <i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i> <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i> 	<ul style="list-style-type: none"> Generally drilling is normal to strike, however the intercept orientation in relation to each pegmatite is yet not determined. Drilling results reported are down hole.

Criteria	JORC Code explanation	Commentary
Diagrams	<ul style="list-style-type: none"> <i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i> 	<ul style="list-style-type: none"> Diagrams are included in the text above. Collar locations mapped in text above.
Balanced reporting	<ul style="list-style-type: none"> <i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i> 	<ul style="list-style-type: none"> All complete results at hand are reported.

Other substantive exploration data	<ul style="list-style-type: none"> • <i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i> 	<ul style="list-style-type: none"> • A maiden Resource was declared in 2010. This was estimated by ordinary kriging at 11.75 Mt (Indicated) @ 1.3% Li2O and 10.47 Mt (Inferred) @1.2% Li2O at a cut-off grade of 0.75% Li2O. • This was declared as a recoverable resource within a Whittle 4X optimisation informed by USD 6000/t Lithium Carbonate price, 45-degree pit slope angle and 70% process recovery. • The “reasonable prospects for economic extraction” requirement generally implies that the quantity and grade estimates meet certain economic thresholds and that the mineral resources are reported at an appropriate cut-off grade considering extraction scenarios and processing recoveries. To meet this requirement, consideration was made that major portions of the project are amenable for open pit extraction. • To determine the quantities of material offering “reasonable prospects for economic extraction” by an open pit, a pit optimizer and reasonable mining assumptions to evaluate the proportions of the block model (Indicated and Inferred blocks) that could be “reasonably expected” to be mined from an open pit was modeled. The optimization parameters were selected based on experience and benchmarking against similar spodumene projects. The reader is cautioned that the results from the pit optimization are used solely for testing the “reasonable prospects for economic extraction” by an open pit and do not represent an attempt to estimate mineral reserves. There are no mineral reserves on the James Bay Lithium Project. The results are used as a guide to assist in the preparation of a mineral resource statement and to select an appropriate resource reporting cut-off grade. • Assumptions Considered for Conceptual Open Pit <ul style="list-style-type: none"> ○ Lithium Carbonate (Li2CO3) price: 6,000 US\$/tonne ○ Lithium Carbonate Li2O content : 40.4 % ○ Off Site Cost (Marketing, etc.) 2.5 % of price ○ Mining Cost 4 US\$/tonne mined ○ Processing 50 US\$/tonne of feed ○ General and Administrative 10 US\$/tonne of feed ○ Mining Dilution 10 percent ○ Mining Loss 5 percent
---	--	--

	<ul style="list-style-type: none">○ Overall Pit Slope 45 degrees○ Process Rate 1,000,000 tonne feed/year○ Li2O Process Recovery 70 percent○ In Situ Cut-Off-Grade 0.65 percent Li2O
--	--

Criteria	JORC Code explanation	Commentary
Further work	<p><i>• The nature and scale of planned further work. Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i></p>	<ul style="list-style-type: none"> • This drilling campaign, once completed, will inform a resource re-estimate at James Bay and DFS study. • Diagrams included in text above. • Further metallurgical test work and drilling planned. • Database compilation ongoing • Baseline scientific work to support EIA commenced and ongoing • Sterilization drilling to commence